



# Series 95



## Series 95 Ordering Chart

<b>Weatherproof Enclosure</b> (for electric switch only) Yes <b>W</b> No <b>No code required</b>
<b>Electric Switch Code</b> See Electric Switch Page
<b>No. of Positions</b> <b>2,3,4</b> (No code required if unrestricted)
<b>Mounting</b> Panel (No code required) Base Mounting Plate <b>1</b>
<b>Connections</b> 1/2" NPT Female <b>F8</b> 1/2" Spigot <b>S8</b> 3/8" Spigot <b>S7</b>
<b>Operators</b> <b>L</b> ever <b>K</b> ey Lever Type
<b>Port Code</b>
<b>No. of Banks</b> <b>1 to 4</b>
<b>Class (See Below)</b>
<b>Class P:</b> Brass Body Stainless Steel Spindle Acetal Resin Stems Fluoro Elastomer Seals
<b>Class R:</b> Brass Body Stainless Steel Spindle PTFE Stems Fluoro Elastomer Seals
<b>Class S:</b> Stainless Steel Body Stainless Steel Spindle Acetal Resin Stems Fluoro Elastomer Seals
<b>Class T:</b> Stainless Steel Body Stainless Steel Spindle PTFE Stems Fluoro Elastomer Seals

**EXAMPLE** 95 P 1 02 L F8 1

**High Flow Capacity**  
Series 95 Valves offer a higher flow capacity than their sister products, 40 & 60 Series.

**Versatility**  
Used in a wide variety of applications this robust product is particularly useful in emergency shut down applications.

**Permutations**  
With the choice of operative, permanently open and permanently closed ports in any of the four positions, plus a spindle with one flat, two adjacent, two opposite, or three flats, the number of permutations in just one bank is clearly enormous.