


Cargo Aids

- This new range of floor pan fittings, designed in accordance with SAE AS8905 (MIL-F-8905B) and MIL-A-21165A, are light-weight yet extremely strong whilst remaining simple to fit and operate.
- Interiors can be changed from cargo-carrying to passenger-carrying duties in a matter of minutes and are simple to fit and operate.
- The units incorporate a seat-stud onto which a standard jaw fitting (MS22034-4) can be secured, and a swivelling ring for use with cargo tie-down devices or webbing-based lashings.
- The fittings are manufactured in the UK in our Aerospace approved manufacturing plant using the latest state of the art techniques.



High Quality Specifications

Designed and manufactured to the highest standards, the floor pan fittings meet or exceed the specifications set forth in SAE AS8905 (MIL-F-8905B) and MIL-A-21165A.

Ease of Operation

Where fitted, lashings can be fixed or tied on to the swivelling ring if required. The Cargo ring folds away into the recess of the floor fitting when not in use for additional safety.

Strength Tested

Sampling of manufactured batches is done in accordance with MIL-STD-105E (similar to BS6001 and ISO 2859) to guarantee safe, quantifiable and consistent performance.

Minimum Specification-Ring and Stud Fitting

■ Part No:		AS21234			
		RING		STUD	
		Vertical pull	54° Pull	Vertical pull	Horizontal Pull
■ Proof Load:	(lbf)	5000	5000	5475	2300
	(daN)	2224	2224	2435	1023
■ Ultimate Design Load:	(lbf)	7500	7500		
	(daN)	3336	3336		
■ Unit weight:		0.475kg/1.0lbs			

Floor Pan Fitting
AS21234
(AS8905/MIL-A-21165A)

The Drallim Group

Leading innovators in technology and quality